

10/593905

1 Substitute Specification  
(clean version)

## DESCRIPTION

## OPTICAL PICKUP DEVICE

## 5 TECHNICAL FIELD

[0001] The present invention relates to a pickup and an optical pickup device that avoids collision of an optical disk.

## BACKGROUND ART

10 [0002] A recording and reproducing device, such as a CD (Compact Disk) player/recorder or a DVD (Digital Video (Versatile) Disk) player/recorder, reads information recorded on an optical disk, such as a CD. In reading information, the recording and reproducing device emits a  
15 light beam from a light source included in a pickup of the recording and reproducing device onto an information recording surface of the optical disk, and detects a reflected light from the information recording surface.

[0003] The pickup also includes an actuator that drive-  
20 controls an objective lens. The objective lens converges the light beam emitted from the light source on the information recording surface. A focal point of the light beam irradiated onto the information recording surface is adjusted according to a distance between the objective lens  
25 and the information recording surface.

[0004] To perform such adjustment of the focal point,

the CD player or the like controls the actuator by focus servo control. The actuator is controlled to drive-control the objective lens in a direction of an optical axis of the objective lens so that the light beam can be focused with  
5 an optimum focal point onto the information recording surface.

[0005]        To irradiate the light beam with the optimum focal point, there is conventionally known a technique that detects a real focal point onto the information recording  
10 surface, and controls a position of the objective lens according to a deviation between the real focal point and an optimum focal point.

[0006]        However, if the detected real focal point is in error, due to say surface warping of the optical disk, a  
15 scratch on the information recording surface or the like, the various problems can occur. For example, the position of the objective lens relative to the optical disk cannot be accurately detected. As a result, the objective lens or the like collides against the information recording surface  
20 of the optical lens. It is, therefore, necessary to accurately detect the position of the objective lens and control movement of the objective lens to avoid collision between the objective lens and the information recording surface.

25 [0007]        A focus controller disclosed in Patent Document 1 determines whether there is a possibility of collision

between the objective lens and the optical disk. Namely,  
the focus controller monitors two factors: a distance  
between the objective lens and the optical disk, and a  
velocity of the objective lens at which the objective lens  
5 approaches the optical disk.

[0008]        Patent Document 1: Japanese Patent Application  
Laid-Open No. 2002-157758

#### DISCLOSURE OF INVENTION

##### 10 PROBLEM TO BE SOLVED BY THE INVENTION

[0009]        In the conventional technique disclosed in the  
Patent Document 1, whether there is a possibility of  
collision between the objective lens and the optical disk  
by detecting the distance between the objective lens and  
15 the optical disk based on a focus error signal; however, a  
range in which the distance can be detected is narrower  
than a range in which the objective lens is moved. As a  
result, the detected distance between the objective lens  
and the optical disk is often in error. Furthermore, the  
20 objective lens is moved for a considerable distance when  
detecting the position of the optical disk performed when  
recording or reproducing of information on or from the  
optical disk is started. As a result, an error in the  
detected distance between the objective lens and the  
25 optical disk can be very conspicuous. If the objective  
lens performs a collision avoidance operation based on a

wrong distance, the focus servo control cannot be closed.

[0010]        The present invention has been achieved to solve  
the conventional problems. It is an object of the present  
invention to obtain an optical pickup device that can  
5 prevent collision between an objective lens and an  
information recording surface of an optical disk.

#### MEANS FOR SOLVING PROBLEM

[0011]        To solve the above problems and to achieve the  
10 above objects, according to the invention disclosed in  
claim 1, an optical pickup device for irradiating a light  
from a light source onto an optical recording medium  
through an objective lens moved in a focal direction by an  
actuator, and for causing a signal detecting unit to  
15 receive a return light from the irradiated light, includes  
an access limit introducing unit that obtains shape  
information on the optical recording medium in a diameter  
direction before recording and/or reproducing is performed  
on the optical recording medium, and that sets limits to  
20 access distances of the objective lens to the optical  
recording medium according to a plurality of positions of  
the optical recording medium in the diameter direction,  
respectively based on the obtained information on the  
shape; and a collision avoiding unit that restricts  
25 movement of the objective lens in the focal direction by  
the actuator based on the plurality of set limits to the

access distances.

[0012]        Moreover, according to the invention disclosed in  
claim 8, a collision preventing method of preventing  
collision between an objective lens moved by an actuator in  
5 a focal direction and an optical recording medium onto  
which a light is irradiated from a light source, includes a  
first step of obtaining shape information on the optical  
recording medium in a diameter direction before recording  
and/or reproducing is performed on the optical recording  
10 medium; a second step of setting limits to access distances  
of the objective lens to the optical recording medium  
according to a plurality of positions of the optical  
recording medium in the diameter direction, respectively  
based on the obtained shape information; and a third step  
15 of restricting movement of the objective lens in the focal  
direction by the actuator based on the plurality of set  
limits to the access distances.

#### BRIEF DESCRIPTION OF DRAWINGS

20 [0013]

Fig. 1 is schematic of a pickup according to a first  
embodiment of the present invention.

Fig. 2 is a block diagram of a disk-collision avoiding  
device according to the first embodiment.

25 Fig. 3 is a flowchart of an operation procedure for  
avoiding collision between an objective lens and an optical

disk.

Fig. 4 is an example of a focus error signal.

Fig. 5 is schematic for explaining the relationship  
between focus drive currents and in-focus states calculated  
5 by the disk-collision avoiding device.

Fig. 6 is a graph for explaining the method of  
calculating thresholds of the focus drive currents.

Fig. 7 is a schematic of a pickup according to a  
second embodiment of the present invention.

10      Fig. 8 is a block diagram of a disk-collision avoiding  
device according to the second embodiment.

Fig. 9 is a schematic for explaining the relationship  
between moving distances of an objective lens and in-focus  
states calculated by the disk-collision avoiding device.

15      Fig. 10 is a schematic of a pickup according to a  
third embodiment of the present invention.

Fig. 11 is a block diagram of a disk-collision  
avoiding device according to the third embodiment.

20      EXPLANATIONS OF LETTERS OR NUMERALS

[0014]

- 1-3    Disk-collision avoiding device
- 10    Pickup
- 15    Signal detecting unit
- 25    16, 46    Objective-lens driving unit
- 20    Objective lens holder

- 21      Focus coil
- 22      Objective lens
- 31      Focus driving unit
- 32      Drive-current detecting unit
- 5       34      Radial-position detecting unit
- 35      Focus control unit
- 36      Threshold calculating unit
- 37      Storing unit
- 42      Moving-distance calculating unit
- 10      45      Position sensor
- 55      Mechanical stopper
- 57      Coil
- 58      Stopper unit
- 59      Mechanical stopper driving unit
- 15      70      Optical disk

BEST MODE(S) FOR CARRYING OUT THE INVENTION

[0015]      Exemplary embodiments of an optical pickup device according to the present invention will be explained hereinafter. The present invention is not limited to the embodiments. Outline and features of the optical pickup device according to the present invention will be explained as the embodiments, and the embodiments of the optical pickup device will be specifically explained.

25      [0016]      [Embodiments]

According to the embodiments of the present invention,



a digital signal recording and reproducing device such as a CD (Compact Disk) player or a CD recorder includes a pickup device (i.e., an optical pickup device) or the like as a device that reads information recorded on an optical disk.

5    The pickup device includes an actuator. The actuator drives an objective lens to control a focus i.e., focal point, of a light beam irradiated onto the optical disk. Furthermore, a disk-collision avoiding device included in the optical pickup device provides control to avoid  
10 collision between a head of an objective lens or the like employed to record or reproduce information on and from an optical recording medium (optical disk) and the optical disk when the information recorded on the optical disk is reproduced or recorded.

15    [0017]        The focal point of the light beam irradiated onto the optical disk is adjusted according to the distance between the objective lens and the optical disk. The objective lens is driven such that the focal point is optimum.

20    [0018]        A focus error signal is a signal indicative of the distance between the objective lens and the optical disk. From the focus error signal, the distance between the objective lens and the optical disk can be detected. Therefore, by using the focus error signal, the collision  
25 between the objective lens and the optical disk can be avoided.



[0019]        Basically, the focus error signal indicates a zero level (to be exact, a zero-crossing point from a maximal point to a minimal point) in an in-focus state in which the focus of the objective lens is on the recording surface. The focus error signal draws an S-curve around the zero level from the maximal point to the minimal point, i.e., a focal point. In addition, the focus error signal exhibits linearity only in a range from the maximal point to the minimal point on one S-curve (which is a range of about ten micrometers from a focal position).

[0020]        Meanwhile, the distance between the objective lens and the optical disk is about several hundreds micrometers to two millimeters when the objective lens is the in-focus state. Therefore, the distance between the objective lens and the optical disk that can be recognized by detecting the focus error signal is far smaller than the range in which the objective lens is moved.

[0021]        Moreover, to control a collision avoidance operation for avoiding collision between the objective lens and the optical disk (an operation of keeping the objective lens away from the optical disk or the like) according to the distance between the objective lens and the optical disk, the following method is known. A threshold of the focus error signal for the collision avoidance operation is set within a capture range (about ten micrometers) of the focus error signal. However, an operation of detecting the

position of the optical disk performed when reproducing of information from the optical disk is started is executed by greatly moving the objective lens. Due to this, when the reproducing of information from the optical disk is started, the focus error signal often exceeds the threshold for determining whether to perform the collision avoidance operation. If the focus error signal exceeds the threshold for determining whether to perform the collision avoidance operation, the objective lens performs the collision avoidance operation. As a result, the focus servo control cannot be closed.

[0022] According to the embodiments of the present invention, the following measures are taken. The relationship between information on a position of the objective lens relative to the pickup device (a focal direction distance) and the focus error signal is obtained in advance as shape information on the optical disk (optical recording medium). A plurality of limits to an access distance (hereinafter, also "access distance limits") of the objective lens to the optical disk are set according to positions of the optical recording medium in a diameter direction. The actuator restricts movement of the objective lens in the focal direction based on the access distance limits, and the collision between the objective lens and the optical disk is avoided.

[0023] For instance, as the information on the position

of the objective lens relative to the pickup device, a drive current for drive-controlling the movement of the objective lens relative to the pickup is used. The drive current can control a moving distance of the pickup according to a magnitude of the drive current.

[0024]        Before recording or reproducing of the information on or from the optical disk, the focus error signal is detected while rotating the optical disk at a predetermined position on a surface of the optical disk.

10    The in-focus state in which the focus of the objective lens is on the recording surface of the optical disk is detected based on the focus error signal. During detection, if a drive current  $I_1$  for moving the objective lens from a neutral position to a position of the in-focus state is measured, the drive current  $I_1$  in the in-focus state can be recognized. Furthermore, the distance between the objective lens and the optical disk in the in-focus state can be calculated from a wavelength of the light beam or the like. A drive current  $I_{wd}$  necessary to move the objective lens by the distance can be calculated. It, therefore, indicates that the objective lens collides against the optical disk when the drive current is equal to  $(I_1 + I_{wd})$ . For this reason, if a threshold (limiter) of the drive current for moving the objective lens is set at the measurement position based on the drive current  $(I_1 + I_{wd})$ , the collision between the objective lens and the optical

disk can be avoided.

[0025]        Thresholds of the drive current (access distance  
limits of the objective lens to the optical disk) are  
calculated at a plurality of locations on the surface of  
5    the optical disk (positions in the diameter direction  
different in a radial position from a center), respectively.  
Thresholds of the drive current on the entire surface of  
the optical disk are calculated based on the relationship  
between the positions of the optical disk in the diameter  
10   direction on the surface of the optical disk and the  
thresholds of the drive current.

[0026]        When the information is actually recorded or  
reproduced on or from the optical disk, the movement or the  
like of the objective lens is controlled based on the  
15   thresholds of the drive current calculated in advance to  
avoid the collision between the objective lens and the  
optical disk if the drive current exceeds the corresponding  
threshold.

[0027]        In this manner, according to the embodiments, the  
20   possible collision between the objective lens and the  
optical disk is detected without using the focus error  
signal during the recording or reproducing processing on  
the optical disk. Due to this, the position of the  
objective lens relative to the optical disk can be  
25   accurately detected even with a surface warping of the  
optical disk or the like, a scratch on the information

recording surface or the like. Accordingly, it is possible to accurately avoid the collision between the objective lens and the optical disk.

[0028]        The use of the disk collision avoiding device is not limited to a CD player or a CD recorder. The disk collision avoiding device can be also applied to a DVD (Digital Video (Versatile) Disk) player, a DVD recorder, a CD drive for a personal computer, a DVD drive for a personal computer or the like.

10            FIRST EMBODIMENT

[0029]        Fig. 1 is a schematic of a pickup according to a first embodiment of the present invention. A pickup 10 is moved in a plane direction parallel to an information recording surface of an optical disk 70 (hereinafter, "radial direction"). The pickup 10 irradiates a light beam onto the information recording surface of the optical disk 70, detects a reflected light from the optical disk 70, and reads information recorded on the optical disk 70.

[0030]        The pickup 10 includes a focus servo mechanism 30, a signal detecting unit 15 that detects a reflected light from a light beam source (not shown) of the light beam irradiated on the optical disk 70, and a disk collision avoiding device 1. The focus servo mechanism 30 includes an objective lens holder 20 and an objective-lens driving unit 16.

[0031]        The objective-lens driving unit 16 includes a

magnet 13, which is a permanent magnet, and a yoke which is not shown. The objective lens holder 20 includes a focus coil 21 and an objective lens 22.

[0032]        An electromagnetic force is generated on the  
5    focus coil 21 by applying a current to the focus coil 21.  
The objective lens holder 20 is moved on the objective-lens driving unit 16 in a light-beam irradiation direction (a direction perpendicular to the surface of the optical disk 70) by an attraction force or a repulsive force between the  
10    electromagnetic force and the magnet 13.

[0033]        The objective lens 22 converges the light beam from the light beam source (not shown) irradiated onto the optical disk 70, and feeds the convergent beam to the optical disk 70. In addition, the objective lens 22 feeds  
15    the light beam reflected by the optical disk 70 to the signal detecting unit 15.

[0034]        The signal detecting unit 15 includes a light receiving element such as a quadripartite detector (not shown). The light receiving element detects the reflected  
20    light of the light beam irradiated onto the optical disk 70 through the objective lens 22 from the optical disk 70.  
The signal detecting unit 15 detects a focus error signal or a reproduced signal from the reflected light from the optical disk 70, and supplies the detected focus error  
25    signal or reproduced signal to the disk collision avoiding device 1 to be explained later. The optical disk 70 is a

recording medium on and from which a CD player/recorder records and reproduces information. The optical disk 70 is a disk such as CD or a DVD.

[0035]        Fig. 2 is a block diagram of the disk collision  
5    avoiding device according to the first embodiment of the present invention. The disk collision avoiding device 1, which avoids the collision of the objective lens 22 against the optical disk 70, includes a focus driving unit 31, a drive-current detecting unit 32, a radial-position  
10   detecting unit 34, and a focus control unit (collision avoiding unit) 35.

[0036]        The focus driving unit 31 is connected to the focus coil 21. The focus driving unit 31 applies a current to the focus coil 21 to drive the objective lens holder 20.  
15   The focus driving unit 31 controls a relative position of the objective lens 22 connected to the focus coil 21 to the pickup 10 by controlling an amount of the current (focus drive current) applied to the focus coil 21. Namely, the focus driving unit 31 can control the relative position of  
20   the objective lens 22 to the optical disk 70 by controlling the amount of the current applied to the focus coil 21.

[0037]        The drive-current detecting unit 32 includes a measuring circuit that measures the amount of the focus drive current (DC component) applied by the focus driving  
25   unit 31 to the focus coil 21. The drive-current detecting unit 32 measures the focus drive current applied by the



focus driving unit 31 to the focus coil 21.

[0038]        The radial-position detecting unit 34 detects a distance of the objective lens 22 in a radial direction from a center of the information recording surface of the optical disk 70 (hereinafter, "radial distance"). The radial-position detecting unit 34 detects the radial distance of the objective lens 22 to the optical disk 70 based on, for example, address information in the reproduced signal read from the optical disk 70.

10 [0039]        The focus control unit 35 includes a threshold calculating unit (an access limit introducing unit) 36 and a storing unit 37. The threshold calculating unit 36 makes the focus drive current and the radial distance of the objective lens 22 in the in-focus state (at a position at which the light beam is in optimum focal point) correspond to each other based on the focus drive current supplied from the drive-current detecting unit 32, the radial distance of the objective lens 22 supplied from the radial-position detecting unit 34, and the focus error signal supplied from the pickup 10.

[0040]        The threshold calculating unit 36 makes the drive current and the radial distance of the objective lens 22 in the in-focus state correspond to each other at a plurality of positions (radial distances) of the optical disk 70. The threshold calculating unit 36 calculates at which position on the surface of the optical disk 70 the

objective lens 22 is in the in-focus state with which focus drive current (calculates a warping of (shape information on) the optical disk 70). The threshold calculating unit 36 calculates thresholds of the focus drive current for the  
5 objective lens 22 based on the following information:  
information at which position the optical disk 70 the objective lens 22 is in the in-focus state with which focus drive current, and the focus drive current (corresponding to the focus drive current Iwd to be explained later)  
10 necessary to move the objective lens 22 in the in-focus state to a position at which the objective lens 22 collides against the optical disk 70.

[0041]      The threshold calculating unit 36 calculates the thresholds of the focus drive current before a reproducing  
15 processing on the optical disk 70. If the focus drive current from the drive-current detecting unit 32 exceeds the corresponding threshold during the reproducing processing on the optical disk 70, the threshold calculating unit 36 transmits, to the focus driving unit 31,  
20 information on a command to control the movement of the focus coil 21.

[0042]      The storing unit 37 stores therein the focus drive current Iwd necessary to move the objective lens 22 in the in-focus state to the position at which the  
25 objective lens 22 collides against the optical disk 70, and the thresholds of the focus drive current calculated before

the reproducing processing on the optical disk 70.

[0043] Operations performed by the respective constituent elements shown in Figs. 1 and 2 will be explained while referring to the flowchart of Fig. 3. The optical disk 70 is inserted into the CD player or the like that includes the disk collision avoiding device 1 (step S100). When the optical disk 70 is inserted into the CD player, the threshold calculating unit 36 starts measuring the warping of the optical disk 70 before the reproducing or recording processing is performed on the optical disk 70.

[0044] The pickup 10 is moved in the plane direction parallel to the surface of the optical disk 70. When the pickup 10 is moved to a predetermined position (a position X1 to be explained later) at which the pickup 10 can read the information recorded on the optical disk 70, the focus control unit 35 transmits, to the focus driving unit 31, information on a command to drive the pickup 10. The focus driving unit 31 that receives the command information from the focus control unit 35 applies the current to the focus coil 21 of the pickup 10. The objective lens holder 20 including the objective lens holder 20 is thereby driven, and the light beam is irradiated onto the optical disk 70 that is being rotated.

[0045] The signal detecting unit 15 extracts the focus error signal from the reflected light from the optical disk 70, and transmits the focus error signal to the threshold

calculating unit 36. Furthermore, the drive-current  
detecting unit 32 measures the focus drive current at time  
when the signal detecting unit 15 extracts the focus error  
signal of zero. The radial-position detecting unit 34  
5 acquires the information (the address or the like of the  
optical disk 70) on the position at which the signal  
detecting unit 15 extracts the focus error signal from the  
reflected light (reproduced light) from the optical disk 70.  
[0046] At this moment, the optical disk 70 is rotated.  
10 By measuring the focus error signal and the focus drive  
current for predetermined time at the position at which the  
focus error signal is extracted, an average focus error  
signal and an average focus drive signal at radial  
positions same in distance from the center are obtained.  
15 [0047] Fig. 4 is an example of the focus error signal.  
In Fig. 4, a horizontal axis indicates the distance  
(irradiation direction distance) between the objective lens  
22 and the surface (signal surface) of the optical disk 70.  
A vertical axis indicates an output of the focus signal.  
20 [0048] The output of the focus error signal (focus error  
output) is changed to draw an S-curve according to the  
distance between the objective lens 22 and the surface of  
the optical disk 70. The signal detecting unit 15 included  
in the pickup 10 is set so that the focus error signal is  
25 equal to zero when the light beam irradiated onto the  
optical disk 70 is in optimum focal point (when the

objective lens 22 is in the in-focus state). Therefore, a distance  $y$  between the objective lens 22 and the surface of the optical disk 70 when the focus error signal is equal to zero is always a constant value (a distance WD to be  
5 explained later).

[0049]        Fig. 5 is a schematic for explaining the relationship between the focus drive current and the in-focus state calculated by the disk-collision avoiding device. The pickup 10 reads the information recorded on  
10 the optical disk 70 in a state in which the optical disk 70 is rotated. The signal detecting unit 15 detects focus error signals at a plurality of positions  $X_1$  to  $X_n$ , respectively, from a closer position (inner position) ( $X_1$ ) to the center of the surface of the optical disk 70 to a  
15 farther position (outer position) ( $X_n$  (where  $n$  is a natural number)) from the center. The drive-current detecting unit 32 measures focus drive currents  $I_1$  to  $I_n$  corresponding to the focus error signal of zero.

[0050]        At the position  $X_n$ , the objective lens 22 turns  
20 into the in-focus state when the objective lens 22 is moved from the objective-lens driving unit 16 (pickup 10) in the light-beam irradiation direction by a distance  $h_n$ . The drive current at this time is assumed as the focus drive current  $I_n$ . It is also assumed that the distance  $h_n$   
25 between the objective-lens driving unit 16 and the objective lens 22 is a distance (distance from the neutral

position) by which the objective lens 22 is moved from the position of the objective lens 22 relative to the objective-lens driving unit 16 when the focus servo control is open (inoperative) to the position in the in-focus state.

5    [0051]

         In the first embodiment, the following instance will be explained. The signal detecting unit 15 detects the focus error signal at the four positions (from the inner position (X1) to the outer position (X4) on the surface of  
10    the optical disk 70. The threshold calculating unit 36 measures the drive currents I1 to I4 corresponding to the focus error signal of zero at the respective positions X1 to X4.

         [0052]      The distance between the objective lens 22 and  
15    the surface of the optical disk 70 is changed according to the warping or deflection of the surface of the optical disk 70 or a mechanical dimensional error of an attachment position of a spindle motor (not shown) or the like. For instance, because of a difference in shape among a  
20    plurality of optical disks 70, distances h1 to h4 by which the objective lens 22 is moved from the objective-lens driving unit 16 to irradiate the light beam with optimum focal point onto the optical disk 70 at the respective positions X1 to X4 differ among the optical disks 70.  
25    Furthermore, because of the warping of the optical disk 70 or the like on the surface of even one optical disk 70, the

distances h1 to h4 differ according to radial positions of the objective lens 22. Due to this, the focus drive currents I1 to I4 for moving the objective lens 22 from the neutral position to the position in the in-focus state  
5 differ on the surface of the optical disk 70.

[0053]      In the first embodiment, the signal detecting unit 15 detects the focus error signal first at the position X1, and the drive-current detecting unit 32 measures the focus drive current at the position X1. In  
10 addition, the radial-position detecting unit 34 acquires information on the position X1 at which the focus error signal is detected, and transmits the information to the focus control unit 35.

[0054]      The pickup 10 is then moved to the radial  
15 position X2 other than the position X1 in the plane direction parallel to the surface of the optical disk 70. At the position X2, similarly to the position X1, the signal detecting unit 15 detects the focus error signal, and the drive-current detecting unit 32 measures the focus  
20 drive signal. In addition, the radial-position detecting unit 34 acquires information on the position X2 and transmits the information to the focus control unit 35.

[0055]      The pickup 10 is further moved to the other radial positions X3 and X4 in the plane direction in  
25 parallel to the surface of the optical disk 70. The signal detecting unit 15 detects the focus error signals at the



positions X3 and X4, respectively. The drive-current  
detecting unit 32 detects the focus drive currents at the  
positions X3 and X4, respectively. The radial-position  
detecting unit 34 acquires information on the respective  
5 positions X3 and X4, and transmits the information to the  
focus control unit 35.

[0056]        The threshold calculating unit 36 makes the focus  
drive currents and the radial distances in the in-focus  
state (at the positions at which the light beam is with  
10 optimum focal point) correspond to each other based on the  
focus drive currents transmitted from the drive-current  
detecting unit 32, the radial distances of the objective  
lens 22 transmitted from the radial-position detecting unit  
34, and the focus error signals transmitted from the pickup  
15 10. In the first embodiment, the focus drive currents at  
which the focus error signal is equal to zero at the  
positions X1 to X4 correspond to the focus drive currents  
I1 to I4, respectively.

[0057]        The storing unit 37 of the focus control unit 35  
20 stores therein the focus drive currents I1 to I4 in the in-  
focus state at the respective positions X1 to X4 as the  
information on the shape (warping) of the optical disk 70  
(step S200).

[0058]        Fig. 6 is a graph for explaining a method of  
25 calculating the thresholds of the focus drive currents.

The distance Wd between the objective lens 22 and the

surface of the optical disk 70 when the focus error signal output is equal to zero (in the in-focus state) is calculated. By doing so, the focus drive current (applied since the objective lens 22 is in the in-focus state until  
5 the objective lens 20 collides against the optical disk 70)  $I_{wd}$  necessary to move the objective lens 22 by the distance  $WD$  can be calculated. Accordingly, the focus drive currents (hereinafter, "collision drive currents") ( $I_1 + I_{wd}$ ) to ( $I_4 + I_{wd}$ ) when the objective lens 22 collides against the  
10 surface of the optical disk 70 at the respective positions  $X_1$  to  $X_4$  can be calculated.

[0059]        As shown in Fig. 6, it is possible to calculate the collision drive currents corresponding to all the radial positions of the objective lens 22 on the optical  
15 disk 70 based on the relationship between the collision drive currents ( $I_1 + I_{wd}$ ) to ( $I_4 + I_{wd}$ ) and the positions  $X_1$  to  $X_4$  by linear interpolation or the like, respectively.

[0060]        In the first embodiment, the threshold calculating unit 36 calculates the relationship between the  
20 collision drive currents ( $I_1 + I_{wd}$ ) to ( $I_4 + I_{wd}$ ) and the positions  $X_1$  to  $X_4$  based on the following information: the focus drive currents  $I_1$  to  $I_4$  in the in-focus state at the respective positions  $X_1$  to 4 (information on the warping of the optical disk), and the focus drive current  $I_{wd}$   
25 necessary to move the objective lens 22 from the surface of the optical disk 70 by the distance  $WD$ .

[0061] The threshold calculating unit 36 calculates the collision drive currents corresponding to all the respective radial positions of the objective lens 22 on the surface of the optical disk 70 as information on the thresholds of the optical drive currents based on the relationship between the collision drive currents ( $I_{11}+I_{wd}$ ) to ( $I_{14}+I_{wd}$ ) and the positions X1 to X4 (step S300). The calculated information on the thresholds of the focus drive currents is stored in the storing unit 37.

10 [0062] Next, the CD drive starts the recording or reproducing processing on the optical disk 70 (step S400). When the pickup 10 is moved to the position at which the reproducing processing or the like is started in the plane direction parallel to the surface of the optical disk 70, 15 the focus control unit 35 transmits, to the focus driving unit 31, the information on the command to drive the pickup 10. The focus driving unit 31 that receives the command information from the focus control unit 35 applies the focus drive current to the focus coil 21 of the pickup 10. 20 The objective lens holder 20 including the objective lens 22 is driven accordingly, and the light beam is irradiated onto the optical disk 70.

[0063] During the recording or reproducing processing on the optical disk 70, the signal detecting unit 15 extracts 25 the reproduced signal from the light beam reflected from the optical disk 70 and transmits the reproduced signal to

the focus control unit 35. At this time, it is unnecessary for the signal detecting unit 15 to extract the focus error signal.

[0064] During the recording or reproducing processing on  
5 the optical disk 70, the drive-current detecting unit 32  
measures the focus drive current. In addition, the radial-  
position detecting unit 34 acquires the information on the  
radial position of the objective lens 22 from the  
reproduced signal transmitted from the signal detecting  
10 unit 15. The focus drive current measured by the drive-  
current detecting unit 32 and the information on the radial  
position of the objective lens 22 acquired by the radial-  
position detecting unit 34 are transmitted to the threshold  
calculating unit 36.

15 [0065] The focus control unit 35 transmits the command  
information to the focus driving unit 31 based on the  
following information: the information on the thresholds of  
the focus drive currents stored before the reproducing  
processing on the optical disk 70, the focus drive current  
20 for the optical disk 70 that current is being measured by  
the drive-current detecting unit 32, and the information on  
the radial positions of the objective lens 22 acquired by  
the radial-position detecting unit 34. In the first  
embodiment, if the focus drive current measured by the  
25 drive-current detecting unit 32 at each radial position of  
the objective lens 22 is close to the collision drive

current stored as the corresponding threshold information by a predetermined value, the focus control unit 35 transmits, to the focus driving unit 31, information on a command to move the objective lens 22 to be farther from the optical disk 70 or on a command to stop the movement of the objective lens 22.

[0066]        Upon reception of the command information from the focus control unit 35, the focus driving unit 31 controls the amount of the current applied to the focus coil 21 based on the information from the focus control unit 35 to avoid the collision between the objective lens 22 and the optical disk 70.

[0067]        When the CD drive finishes the recording or reproducing processing on the optical disk 70 and the optical disk 70 is discharged from the CD drive, the threshold information on the drive currents stored in the threshold calculating unit 36 is deleted (step S500). Alternatively, after the CD drive finishes the recording or reproducing processing on the optical disk 70, the threshold information on the drive currents stored in the threshold calculating unit 36 may be stored in the storing unit 37 until the optical disk 70 is discharged from the CD drive. By doing so, if the CD drive is turned on again after supply of power to the CD drive is stopped, it is unnecessary for the threshold calculating unit 36 to calculate again the threshold information on the drive

currents. If the CD drive is turned on again after the supply of the power to the CD drive is stopped, the threshold information stored in the storing unit 37 is transmitted to the threshold calculating unit 36. The CD drive performs the recording or reproducing processing on the optical disk 70 based on the threshold information of the threshold calculating unit 36.

[0068] The focus drive currents differ in the distance, by which the objective lens 22 can be moved, according to frequencies. Due to this, if the focus drive currents at different frequencies are used, the focus control unit 35 is configured to include an equalizer or the like that corrects each focus drive current.

[0069] Moreover, in the first embodiment, the focus  
15 error signal is detected before the recording or  
reproducing processing on the optical disk 70 while the  
focus servo control is closed. Alternatively, the focus  
error signal can be detected while focus servo control is  
open. In this alternative, the in-focus state is detected  
20 by detecting the focus drive signals detected by the drive-  
current detecting unit 32 and the zero level of the focus  
error signal. This can reduce the misdetection of the  
focus error signal when the warping of the optical disk 70  
is detected.

25     [0070]     In this manner, according to the first embodiment,  
the thresholds of the focus drive currents are calculated

before the recording or reproducing processing on the optical disk 70. Therefore, during the recording or reproducing processing on the optical disk 70, the distance between the objective-lens driving unit 16 and the objective lens 22 in the optical axis direction can be calculated by detecting the focus drive current. This makes it possible to estimate the irradiation direction distance of the objective lens 22 to the optical disk 70, and to reduce the misdetection of the irradiation direction distance of the objective lens 22 to the optical disk 70. Therefore, possibility of collision between the objective lens 22 and the optical disk 70 can be accurately estimated and the collision can be avoided. Furthermore, even while the focus servo control is open (inoperative), the collision between the objective lens 22 and the optical disk 70 can be avoided by detecting the focus drive currents.

#### SECOND EMBODIMENT

[0071]      A second embodiment of the present invention will be explained with reference to Figs. 7 and 8. In the second embodiment, a position sensor (distance measuring unit) 45 detects the distance between the objective lens 22 and the objective-lens driving unit 16 in a laser irradiation direction.

[0072]      Fig. 7 is a schematic of a pickup according to the second embodiment. Fig. 8 is a block diagram of a disk



collision avoiding device. In Figs. 7 and 8, constituent elements that fulfill the same functions as those of the pickup 10 and the disk collision avoiding device 1 according to the first embodiment shown in Figs. 1 and 2 are denoted by the same reference symbols, and will not be repeatedly explained.

[0073]        As shown in Fig. 7, an objective-lens driving unit 46 of the pickup 10 includes the position sensor 45. The position sensor 45 detects the (irradiation direction) position of the objective lens 22 relative to the pickup 10 when the signal detecting unit 15 detects the focus error signal. The position of the objective lens 22 detected by the position sensor 45 is transmitted to a disk collision avoiding device 2 as an electric signal.

[0074]        As shown in Fig. 8, the disk collision avoiding device 2 includes a moving distance calculating unit (moving distance measuring unit) 42. The moving distance calculating unit 42 calculates the electric signal transmitted from the position sensor 45 as a moving distance of the objective lens 22 relative to the objective-lens driving unit 16 using a measuring circuit which is not shown. The moving distance calculated by the moving distance calculating unit 42 is transmitted to the focus control unit 35.

[0075]        The threshold calculating unit 36 calculates thresholds of moving amounts of the objective lens 22 used

to control the movement of the objective lens 22 (access distance limits of the objective lens 22 to the optical disk 70) based on the following information: the focus error signals calculated by the signal detecting unit 15, the moving distance of the objective lens 22 relative to the pickup 10 calculated by the moving distance calculating unit 42, and the information on the positions X1 to X4 acquired by the radial-position detecting unit 34.

[0076]        A procedure for avoiding collision between the objective lens 22 and the optical disk 70 in the second embodiment is the same as that explained in the first embodiment and will not be, therefore, explained. In the second embodiment, a method of calculating thresholds of moving amounts used to control the warping of the optical disk 70 and the movement of the objective lens 22, which method differs from the first embodiment, will be explained.

[0077]        Fig. 9 is an explanatory view of the relationship between focus drive currents and in-focus states calculated by the disk-collision avoiding device. The pickup 10 reads the information recorded on the optical disk 70 while the optical disk 70 is rotated. The signal detecting unit 15 detects focus error signals at a plurality of positions X1 to Xn, respectively from the inner position (X1) to the outer position (Xn (where n is a natural number)). The position sensor 45 detects positions of the objective lens 22 relative to the objective-lens driving unit 16. The

moving distance calculating unit 42 calculates distances between the objective-lens driving unit 16 and the objective lens 22 at the respective positions detected by the position sensor 45.

5    [0078]        At the position  $X_n$ , if the distance between the objective-lens driving unit 16 and the objective lens 22 is  $W_n$ , it is assumed that the objective lens 22 is in an in-focus state. It is also assumed that the distance  $W_n$  between the objective-lens driving unit 16 and the  
10 objective lens 22 is a distance (distance from the neutral position) by which the objective lens 22 is moved from the position of the objective lens 22 relative to the objective-lens driving unit 16 when the focus servo control is open (inoperative) to the position in the in-focus state.

15   [0079]        In the second embodiment, the following instance will be explained. The signal detecting unit 15 detects the focus error signal at the four positions (from the inner position ( $X_1$ ) to the outer position ( $X_4$ ) in the plane direction parallel to the surface of the optical disk 70.

20   The moving distance calculating unit 42 calculates distances  $W_1$  to  $W_4$  between the objective-lens driving unit 16 and the objective lens 22 corresponding to the focus error signal of zero at the respective positions  $X_1$  to  $X_4$ .

         [0080]        Because of a difference in shape among a  
25 plurality of optical disks 70, distances by which the objective lens 22 is moved from the objective-lens driving

unit 16 to irradiate the light beam with optimum focal point onto the optical disk 70 at the respective positions X1 to X4 differ among the optical disks 70. Furthermore, because of the warping or the like of the optical disk 70 on the surface of even one optical disk 70, the distances differ according to the radial positions of the objective lens 22.

[0081] In the second embodiment, the signal detecting unit 15 detects the focus error signal first at the position X1, and the moving distance calculating unit 42 calculates the distance between the objective-lens driving unit 16 and the objective lens 22 at the position X1. In addition, the radial-position detecting unit 34 acquires the information on the position X1 at which the focus error signal is detected, and transmits the information to the focus control unit 35.

[0082] The pickup 10 is then moved to the radial position X2 other than the position X1 in the plane direction parallel to the surface of the optical disk 70.

20 At the position X2, similarly to the position X1, the signal detecting unit 15 detects the focus error signal, and the moving distance calculating unit 42 calculates the distance between the objective-lens driving unit 16 and the objective lens 22. In addition, the radial-position

25 detecting unit 34 acquires information on the position X2 and transmits the information to the focus control unit 35.

[0083]        The pickup 10 is further moved to the other radial positions X3 and X4 in the plane direction parallel to the surface of the optical disk 70. The signal detecting unit 15 detects the focus error signal at the positions X3 and X4, respectively. The moving distance calculating unit 42 calculates the distances between the objective-lens driving unit 16 and the objective lens 22 at the respective positions X3 and X4. The radial-position detecting unit 34 acquires information on the respective positions X3 and X4, and transmits the information to the focus control unit 35. At the positions X1 to X4, the distances between the pickup 10 and the objective lens 22 when the focus error signal is equal to zero correspond to the distances W1 to W4 between the objective-lens driving unit 16 and the objective lens 22, respectively.

[0084]        The storing unit 37 of the focus control unit 35 stores therein the distances W1 to W4 between the objective-lens driving unit 16 and the objective lens 22 in the in-focus state at the respective positions X1 to X4 as the information on the shape (warping) of the optical disk 70.

[0085]        A distance WD between the objective lens 22 and the surface of the optical disk 70 when the focus error output is equal to zero (in the in-focus state) is calculated. By doing so, the distances between the objective-lens driving unit 16 and the objective lens 22

(hereinafter, "collision moving distances") ( $W1+WD$ ) to ( $W4+WD$ ) if the objective lens 22 collides against the surface of the optical disk 70 at the positions  $X1$  to  $X4$  can be calculated, respectively.

5 [0086] This makes it possible to calculate the collision moving distances corresponding to all the radial positions of the optical disks 70 by the linear interpolation or the like based on the relationship between the collision moving distances ( $W1+WD$ ) to ( $W4+WD$ ) and the positions  $X1$  to  $X4$ ,  
10 respectively.

[0087] The threshold calculating unit 36 calculates the collision moving distances corresponding to all the radial positions on the surface of the optical disk 70 based on the relationship between the collision moving distances  
15 ( $W1+WD$ ) to ( $W4+WD$ ) and the positions  $X1$  to  $X4$ , respectively as information on thresholds of the distances between the objective-lens driving unit 16 and the objective lens 22. The threshold calculating unit 36 stores the calculated threshold information in the storing unit 37.

20 [0088] Subsequently, similarly to the first embodiment, the focus control unit 35 transmits, to the focus driving unit 31, information on a command to avoid the collision between the objective lens 22 and the optical disk 70 if the moving amount of the objective lens 22 calculated by  
25 the moving distance calculating unit 42 exceeds the threshold of the moving distance calculated in advance



during the reproducing processing on the optical disk 70.

The focus driving unit 31 applies a predetermined current to the focus coil 21 in response to the command information from the focus control unit 35. In addition, the focus  
5 driving unit 31 controls the position of the objective lens 22 to avoid the collision between the objective lens 22 and the optical disk 70.

[0089]        In this manner, according to the second embodiment, the thresholds of the focal direction distances  
10 between the objective-lens driving unit 16 and the objective lens 22 are calculated before the recording or reproducing processing on the optical disk 70. Therefore, during the recording or reproducing processing on the optical disk 70, the irradiation direction distance of the  
15 objective lens 22 to the optical disk 70 can be calculated by detecting the distance between the objective-lens driving unit 16 and the objective lens 22. This makes it possible to reduce misdetection of the irradiation direction distance of the objective lens 22 to the optical  
20 disk 70. Therefore, the collision between the objective lens 22 and the optical disk 70 can be accurately estimated and the collision can be avoided. Furthermore, even while the focus servo control is open (inoperative), the collision between the objective lens 22 and the optical  
25 disk 70 can be avoided by detecting the focal direction distance of the objective lens 22 relative to the optical



disk 70.

### THIRD EMBODIMENT

[0090]      A third embodiment of the present invention will be explained with reference to Figs. 10 and 11. In the third embodiment, a position of a movable mechanical stopper is controlled to avoid the collision between the objective lens 22 and the optical disk 70. Fig. 10 is a schematic of a pickup according to the third embodiment. Fig. 11 is a block diagram of a disk collision avoiding device. In Figs. 10 and 11, constituent elements that perform the same functions as those of the pickup 10 according to the first embodiment shown in Fig. 1 and the disk collision avoiding device according to the first embodiment shown in Fig. 2 are denoted by the same reference symbols, and will not be repeatedly explained.

[0091]      As shown in Fig. 10, the objective-lens driving unit 46 of the pickup 10 includes a mechanical stopper (movable stopper) 55. The mechanical stopper (movable stopper) 55 includes a magnet 56, a coil 57, and a stopper unit 58. The stopper unit 58 of the mechanical stopper 55 stops the movement of the objective lens 22 to prevent the objective lens 22 from being moved by a distance larger than a predetermined distance relative to the pickup 10. An electromagnetic force is generated on the coil 57 of the mechanical stopper 55 by causing the focus control unit 35 to apply a current to the coil 57. The stopper unit 58

connected to the coil 57 is moved on the objective-lens driving unit 46 in the light-beam irradiation direction by an attraction force or a repulsive force between the electromagnetic force and the coil 57.

5    [0092]        As shown in Fig. 11, a disk collision avoiding device 3 includes a mechanical stopper driving unit 59. The mechanical stopper driving unit 59 is connected to the mechanical stopper 55. By applying the current to the coil 57 of the mechanical stopper 55, the mechanical stopper  
10 driving unit 59 drive-controls movement of the stopper unit 58 relative to the pickup 10.

[0093]        In the third embodiment, if the focus drive current calculated by the drive-current detecting unit 32 exceeds the threshold of the corresponding collision drive  
15 current calculated in advance during the reproducing processing on the optical disk 70, the focus control unit 35 transmits, to the mechanical stopper driving unit 59, information on a command to move the stopper unit 58 to a position at which the objective lens 22 does not collide  
20 with the optical disk 70. The mechanical stopper driving unit 59 controls the position of the stopper unit 58 by controlling the current applied to the coil 57, and avoids the collision between the objective lens 22 and the optical disk 70. For instance, if a focus drive current  $I_z$   
25 calculated by the drive-current detecting unit 32 exceeds the collision drive current  $(I_{l1}+I_{wd})$  calculated in advance

at the position X1 during the reproducing processing on the optical disk 70, the mechanical stopper driving unit 59 moves the stopper unit 58 to a position at which the objective lens 22 is moved from the position in the in-focus state to a position at which a moving distance of the objective lens 22 does not exceed the distance WD in a direction of the optical disk 70.

[0094]        By doing so, even if the focus drive current detected by the drive-current detecting unit 32 exceeds the threshold of the corresponding focus drive current calculated in advance during the reproducing processing on the optical disk 70, the objective lens 22 collides only against the stopper unit 58. The collision between the objective lens 22 and the optical disk 70 can be, therefore, avoided. Alternatively, the pickup 10 according to the second embodiment may include the mechanical stopper 55, and the disk collision avoiding device 2 may include the mechanical stopper driving unit 59.

[0095]        In this manner, according to the third embodiment, even if the focus drive current exceeds the threshold of the corresponding focus drive current calculated in advance during the reproducing processing on the optical disk 70, the position of the stopper unit 58 in the irradiation direction is controlled. Therefore, the objective lens holder 20 or the like collides only against the stopper unit 58, and it is possible to ensure avoiding the

collision of the objective lens 22 against the optical disk  
70.